

QMTS2.E55656

Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

Material Dsg	Color	Build up		R.T.I.		H				Meets 746E DSR
		Min Thk (mm)	Flame Class	Elec (°C)	Mech (°C)	W	A	V	C	
HB-77	ALL	0.71	HB	115	110	4	0	-	-	-
		1.57	HB	115	110	3	0	-	0	-
K-57	ALL	0.74	HB	-	-	-	-	-	-	-
		1.60	HB	-	-	-	-	-	-	-
NF-77(BK)	BK	0.50	V-0	50	50	0	0	-	-	-
		0.80	V-0	50	50	0	0	-	3	-
NF-77(N)	GY	0.25	V-0	-	-	0	0	-	-	-
		0.38	V-0	-	-	0	0	-	-	-
		0.80	V-0	-	-	0	0	-	-	-
		1.60	V-0	-	-	0	0	-	1	-
NF-77(R)	BN	0.25	V-0	90	90	0	3	-	-	-
		0.80	V-0	90	90	0	3	-	-	-
		1.60	V-0	90	90	0	4	-	2	-
RK-76	GN	0.74	HB	-	-	-	-	-	-	-
		1.60	HB	-	-	-	-	-	-	-
NFL	NC	0.18	V-0	-	-	-	-	-	-	-
		0.27	V-0	-	-	-	-	-	-	-
		0.91	V-0	-	-	-	-	-	-	-
		1.61	V-0	-	-	-	-	-	-	-
RK-76(S)	NC,GN,RD	0.80	HB	-	-	-	-	-	-	-
		1.60	HB	-	-	-	-	-	-	-